



# accumulators & pulsation dampeners

## Variopress Pressure Variator



- 3000 psi Max. Pressure
- 5.5 gpm Max. Flow
- 176°F Max. Temperature
- 1/4" BSP-F Inlet
- 1/4" BSP-F Outlet
- 6.4 oz Weight

For use with hot water systems to reduce pressure at the gun (without going back to the machine). Variopress restricts the flow to the nozzle, temporarily raising the pressure and causing the unloader to bypass the flow. Can also be used to create steam.

Product No.	Description
VARIOPRESS	Pressure Variator

## Flow Regulator



- 3650 psi Max. Pressure
- 8.0 gpm Max. Flow
- 320°F Max. Temperature
- 1/4" BSP-M Inlet
- 1/4" BSP-F Outlet
- 6.7 oz Weight

Product No.	Description
FRI	Flow Regulator

## Pressure Accumulator



- 1350 psi Max. Pressure
- 8.0 gpm Max. Flow
- 90 to 120 psi Max. Charge
- 3/4" BSP-M Inlet
- 0.6 lbs Weight

Product No.	Description
AIPO	Pressure Accumulator

## Pulsation Dampener



- 1000 psi Max. Charge Pressure
- 1/2" to 1" NPT-F Connection

Product No.	Description
33750015	30.0 cu.in 1" NPT-F
33750017	7.4 cu.in 1/2" NPT-F

## Pulsation Dampener



- 3050 psi Max. Pressure
- 580 psi Max. Charge Pressure
- 11.8 oz Volume
- 1/2" NPT-F Connection
- 5.9 lbs Weight

Product No.	Description
PDH	Pulsation Dampener

## Pulsation Dampener



- 2150 to 3050 psi Rated Pressure
- 16.0 to 43.0 gpm Max. Flow
- 1/2" BSP-M Connection (A4X)
- 3/4" BSP-M Connection (A7X)
- Stainless Steel Construction

Product No.	Pressure	Max Flow
A4X	3050 psi	16.0 gpm
A7X	2150 psi	43.0 gpm

## Pulsation Dampener



- 3050 to 4750 psi Rated Pressure
- 43.0 to 195.0 gpm Max. Flow
- 1/2" BSP-M Inlets (A7, A7S)
- 3/4" BSP-M Inlets (A15)
- Forged Steel Construction

Product No.	Pressure	Max Flow
A7	3050 psi	43.0 gpm
A7S	4750 psi	43.0 gpm
A15	4750 psi	195.0 gpm

**Having Trouble with your Installation?**

**Call Us for Technical Assistance or Help with Product Selection.**