

## Hannay Series 1000 Hose Reels

**Typical Applications:**

- Pressure Washing
- Washdown
- Spray Washing
- Air



- Compact Manual Rewind Hose Reel
- Handles Single 1/4" and 3/8" ID hose
- Includes Adjustable Spring Tension Brake
- Standard 3/8" FPT Outlet
- 3000 psi Maximum Operating Pressure

Product No.	Hose Capacity (with 3/8" ID Hose)
10201416	175 ft.
10161416	100 ft.
10141416	75 ft.

## Hannay Series 1500 Hose Reels

**Typical Applications:**

- Lawn Care
- Agriculture
- Pest Control
- Steam Cleaning



- Manual or power rewind hose reel
- Handles single 1/4" and 5/8" ID hose
- Manual:
  - A direct crank rewind is permanently attached to the reel axle
- Power:
  - A chain and sprocket drive is powered by an electric motor
- Strong, lightweight & compact design
- Standard 1/2" NPT Outlet
- 3000 psi Maximum Operating Pressure

Product No.	Rewind Style	Hose Capacity (with 3/8" ID Hose)
15141718	Manual	150 ft.
15201718	Manual	300 ft.
15261718	Manual	450 ft.
15301718	Manual	550 ft.
15141718E12V	12 Volt Electric	150 ft.
15201718E12V	12 Volt Electric	300 ft.
15261718E12V	12 Volt Electric	450 ft.
15301718E12V	12 Volt Electric	550 ft.

## Hannay Series N700 Hose Reel

**Typical Applications:**

- Lubrication
- Air/Water
- Washdown
- Air Tools
- General Industrial,
- Assembly Operations



- Spring Rewind
- Narrow frame & compact mounting base
- Handles single 3/8" and 1/2" ID hose
- Heavy duty spring motor provides self-contained rewind power
- Standard inlet is 90° swivel joint with 1/2" NPT thread standard 1/2" NPT outlet
- 3000 psi Maximum Operating Pressure

Product No.	Hose Capacity (with 3/8" ID Hose)
N7161617C	35 ft.
N7161920J	50 ft.
N7162324J	65 ft.
N7162625B	75 ft.
N718252615.5B	100 ft.
718303120D	150 ft.

## Hannay Stainless Steel 1000 Hose Reel


**Typical Applications:**

- Washdown
- Air Tools
- Pressure Washing
- Spray Operations,
- Steam Cleaning



- Compact manual rewind hose reel
- Direct crank rewind
- Lightweight & compact
- For use with 1/4" to 3/8" ID hose
- Frame, discs, drum & internal parts made from 304 stainless steel
- Smooth grey polished mill finish
- Standard adjustable cam lock brake
- Standard 3/8" FPT Outlet
- 3000 psi Max. Operating Pressure
- 90° Swivel Joint
- 1/2" NPT-F Inlet
- 3/8" NPT-F Outlet
- +20° F to +400° F Max. Temperature

Product No.	Dimensions & Hose Capacity (with 3/8" ID Hose)
SS10141416	14" L x 6" W x 15.75" H (75 ft.)
SS10161416	14" L x 8" W x 15.75" H (100 ft.)
SS10201416	14" L x 12" W x 15.75" H (175 ft.)



# hose reels components

## Hannay Pressure Wash Hose Reel

- 4000 psi Max. Pressure
- 250°F Max. Temperature
- 1/2" NPT Inlet
- 3/8" NPT-F Outlet
- Adjustable cam lock brake assembly
- Direct crank rewind
- Handles 150 feet of 3/8" ID hose



Product No.	Description
PW2	Hose Reel
PWK400	Wall Mount Kit (incl. platform, knob & mounting hardware)

## Hannay GH1100 Portable Hose Reel on Wheels

### Typical Applications:

- Restaurants
- Hotels
- Agriculture
- Home Use
- Grounds Maintenance




- Continuous flow reel with swivel joint inlet, fluid hub & outlet riser
- Handles 3/8" and 5/8" ID hose
- Direct crank rewind and cam lock brake
- Garden hose thread
- One piece foot, rubber tires & removable steel handle bar
- Inlet - 90° 1/2" female NPT swivel, 1/2" female NPT inlet/outlet
- 3000 psi Max. Pressure
- +20°F to +400°F Max. Temperature

Product No.	Dimensions & Hose Capacity
GH1100	Manual Rewind, 300 ft. Hose Capacity, 3/8" ID Hose, 22" L x 21.5"W x 39"H

## Economical Hose Reels

- Steel construction
- 3000 psi Max. Pressure



Product No.	Replacement Swivel	Hose Capacity (3/8" ID Hose)	Dimensions (with Handle)		
			L	W	H
HR50	SW13H202	50 ft.	14	10.5	13.5
HR100	SW13H201	100 ft.	19	11	13
HR150	SW13H208	150 ft.	17	13.5	16.5
HR200	SW13H206	200 ft.	20	16.5	20
HRRKIT	Swivel O'Ring Repair Kit				
HDWARE	Handle Repair Kit				

## Hannay GHAT1200 Portable Hose Reel on Wheels

### Typical Applications:

- Lubrication,
- Air/Water,
- Washdown,
- Air Tools,
- General Industrial
- Assembly Operations



- Continuous flow reel with swivel joint inlet, fluid hub & outlet riser
- Handles 1/2" and 1" ID hose
- Direct crank rewind and cam lock brake
- Garden hose thread
- One piece foot, rubber tires, removable handle bar
- Inlet - 90° 1/2" female NPT swivel, 1/2" female NPT inlet/outlet
- 3000 psi Max. Pressure
- +20°F to +400°F Maximum Temperature

Product No.	Dimensions & Hose Capacity
GHAT1200	Manual Rewind, 350 ft. Hose Capacity, 1/2" ID Hose, 23" L x 24.88"W x 30"H

## Heavy Duty 4000 PSI Hose Reel



- 250°F Max. Temperature
- 4000 psi.
- Direct Crank Rewind
- Solid Steel Construction with Durable Powder Coat Paint
- Full Flow Swivel Brass Joint
- Mounting Bracket Included
- 3 Foot High Pressure Hose
- Pigtail with Swivel Arm for Ease of Connection

Product No.	Description
HR40150HD	4000 PSI Hose Reel

**We Offer the Full Line of Hannay Hose Reels.**

**Please Contact Us for Complete Details.**

**NEW!**

## Stainless Steel Hose Reel 5000 PSI



- 400°F Max. Temperature
- 5000 psi.
- Stainless Steel Hub with Steel Arm and Accessories
- Dimensions L18" x W18" x H24"
- 150 ft Hose Capacity
- 3/8" NPT-F Inlet

Product No.	Description
SHR50150	Stainless Steel Hose Reel 5000 PSI Hose Reel

Maritimes/Quebec/Ontario

Phone TOLL FREE: 1.888.881.6667  
Fax TOLL FREE: 1.800.350.5666

A28

[www.pressurewashcomponents.ca](http://www.pressurewashcomponents.ca)

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592  
Fax TOLL FREE: 1.800.661.3719