

# nozzles components

## Tank Washing Nozzles

- PA offer a wide variety of quality Tank Washing Nozzles suitable for a wide range of applications.
- All Tank Washing Nozzles are custom built to ensure performance satisfaction.

### MI63 Hydraulic Driven Tank Cleaner



- 2000 psi Max. Pressure
- 195° F Max. Temperature
- 3/4" BSP-F Inlet
- Minimum Overall Coverage 1.8" (45mm)
- Nozzle Type – 4 x M4 \*

Product No.	Length	GPM
25460024P	35.4"	6.6 gpm

\* nozzles not included

### M63E/M63P Self-Propelled Tank Cleaner




- 2000 psi Max. Pressure
- 195° F Max. Temperature
- 3/4" BSP-F Inlet
- Minimum Overall Coverage 1.8" (45mm)
- Nozzle Type – 4 x M4 \*

Product No.	Propulsion	Length	GPM
25450004P	Electric (24V AC Max.Voltage)	35.4"	10.5 gpm
25452004P	Air-driven	35.4"	10.5 gpm
25452604P	Air-driven	25.6"	10.5 gpm

\* nozzles not included

### A42FR2 Cleaning Head



- 580 - 2000 psi Max.Pressure
- 5.3 - 16.0 gpm Max. Flow
- 195°F Max. Temperature
- Stainless Steel and Anodized Aluminum Construction
- Nozzle Type - 3-1/4" NPT \*
- Ideal for car wash industry

Product No.	Max.Size
25515020P	5.3 gpm
25515026P	8.0 gpm
25515040P	10.6 gpm
25515033P	16.0 gpm

\* nozzles not included



### A80R Self-Propelled Tank Cleaner



- 2000 psi Max. Pressure
- 195° F Max. Temperature
- 3/4" BSP-F Inlet
- Nozzle type – 4 x 1/4 npt \*
- 303 Stainless Steel Construction
- 20 min.-1 Max.RPM
- 6.4" (165mm) Minimum Overall Coverage

Product No.	Description
25482020P	6.6 maximum GPM
25482025P	8.0 maximum GPM
25482030P	10.5 maximum GPM
25482040P	13.2 maximum GPM
25482050P	17.2 maximum GPM
25482060P	21.0 maximum GPM
25482070P	26.5 maximum GPM
25482080P	29.0 maximum GPM
25482090P	31.7 maximum GPM
25482200P	Protection cage for A80R (fixing screws & nuts included)

\* nozzles not included