

pump drive accessories

RS99 Gear Reducer

- 3400 RPM Max. Engine Speed
- 5.0 hp Max. Engine Output
- 1450 RPM Pump Speed
- 2.4:1 Reduction Ratio
- 3/4" Diameter Keyed Engine Shaft
- Eliminates Belts and Pulleys
- Right or Left Hand Reversible Mount

Mounts to engines with (4) 5/16" threaded holes on 3.62 diameter bolt circle.
See SAE specification J609A for additional information on engine mounting dimensions. Fits Interpump models: T521, 531, 731, 721, 701, 911, 981, 991.

Product No.	*Description*
RS99	Gear Reducer

NEW! RS500 & RS500H Gear Reducer

- Gear Reducer for Gas or Diesel Engines
- 3100 RPM Max. Engine Speed
- 25 HP Max. Engine Output
- 1425 RPM Pump Speed
- 1:2.2 Reduction Ration
- Pump Series 47, 47HT, 47SS, 66, 66HT and 66SS

Product No.	*Description*
RS500*	Gear Reducer
RS500H	Gear Reducer for HONDA Engines

*RS500 Replaces RS151

PTO Gear Multiplier

- 550 RPM PTO
- 1:1:9 Multiplier
- 1-3/8" Splined Shaft
- Up to 10.0 hp Pumps
- 9.5 lbs Weight

Fits Interpump models:
T-921, T1011B, T1311.T1321, T1511, T1621, T2011

Product No.	*Description*
MPTO	Gear Multiplier

Aluminum Pulleys

- 2, 3 and 4-Groove
- 100, 140 & 160 mm Diameter
- 24 or 32 mm Bore

Product No.	*Groove*	*Diameter*	*Bore*
2PY100A24	2	100 mm	24 mm
2PY140A24	2	140 mm	24 mm
2PY160A24	2	160 mm	24 mm
3PY140A24	3	140 mm	24 mm
4PY140B32	4	140 mm	32 mm

Flex Couplers



Product No.	*Shaft Dimension*
FC56C2405	24 mm x 5/8"
FC145TC2407	24 mm x 7/8"
FC184TC2409	24 mm x 1-1/8"
FC213215TC2411	24 mm x 1-3/8"
FCL1002408L	24 mm x 1" (for MFG811)
FCL1992409	24 mm x 1-1/8"

Mounting Flanges

- Ensure Pump and Motor RPM's
- Match When Selecting Flanges.

Product No.	*HP*	*Motor Frame*
MF56145C	2.0	56C, 145TC, 182C
MF184TC	3.0	184TC
MF213215TC	7.5	213TC, 215TC, 184TC
MFG811	11.0	Gas Engine