



switches

Stopmatic



- 145 psi Max. Pressure
- 4.75 gpm Max. Flow
- 140°F Max. Temperature
- 1/2" BSP-M Inlet
- 1/2" BSP-M Outlet
- 250V, 1.0A
- Total stop in low pressure mode

Product No.	Description
STOPMATIC	Stopmatic Switch

Flow Switch



- 4000 psi Max. Pressure
- 12.0 gpm Max. Flow
- 108°F Max. Temperature
- 3/8" NPT-F Inlet
- 3/8" NPT-F Outlet

Product No.	Description
GP100879	Flow Switch

103012PV Flow Switch (GP100329)



- 4000 psi Max. Pressure
- 18.7 gpm Max. Flow
- 0.75 gpm Min. Flow
- 195°F Max. Temperature
- 3/8" NPT-F Connections
- 250V, 3.0A
- 40.0 oz Weight

Product No.	Description
103012PV	Flow Switch

FSI Flow Switch



- 3650 psi Max. Pressure
- 8.0 gpm Max. Flow
- 175°F Max. Temperature
- 3/8" BSP-M Connection
- 230V, 3.0A
- 10.2 oz Weight

Product No.	Description
FSI	FSI Flow Switch
28051823P	Replacement Probe

FL7N Flow Switch



- 5100 psi Max. Pressure
- 8.0 gpm Max. Flow
- 1.06 gpm Min (Vertical)
- 0.8 gpm Min (Horizontal)
- 175°F Max. Temperature
- 3/8" BSP-M Connection
- 230V, 3.0A

Product No.	Description
FL7N	FL7 Flow Switch
28051823P	Replacement Probe

Reedless Inline Flow Switch



- 5.0A Micro Switch
- Minimum Flow 0.5 gpm activation
- 48", 18 AWG lead
- No spring, uses magnets for all movements
- 180°F Max. Temp
- 3/8" NPT-F Outlet/Outlet
- 250 VAC Voltage

Product No.	Description
GP100934	Brass inline flow switch - 12 gpm/5000 psi
GP100953	SS inline flow switch - 12 gpm/5800 psi

Simplex3 Pressure Switch



- 3000 psi Max. Pressure
- 725 psi Min. Pressure
- 435 psi Switching Pressure
- 21.0 gpm Max. Flow
- 1/4" BSP-M Inlet
- 250V, 1.0A

Product No.	Description
SIMPLEX3	Simplex3 Switch

PSW1-15B Pressure Switch



- 3650 psi
- 220 psi Switching Pressure
- 195°F Max. Temp.
- 250V, 16.0A
- 1/4" BSP Connection

Product No.	Description
PSW1-15B	Pressure Switch - 15 bar.



PR16SS Stainless Steel Pressure Switch



- 3650 psi Max. Pressure
- 360 psi Switching Pressure
- 195°F Max. Temperature
- 250V, 15.0A
- 9.2 oz Weight

Product No.	Description
29003552P	1/4" NPT Connection(SS)
29004824P	Repair Kit
12500000P	Switch

PR1 Pressure Switch



- 5800 psi Max. Pressure
- 650 psi Switching Pressure
- 195°F Max. Temperature
- 3/8" BSP-M Connection
- 250V, 15.0A
- 10.2 oz Weight
- Stainless Steel

Product No.	Description
PSW2	PR1 Pressure Switch (Black)
29002424P	Repair Kit (10 pieces)
12500100P	Switch
29002624P	Repair Kit (1 piece)

PR16 Pressure Switch



- 3650 psi Max. Pressure
- 580 psi Switching Pressure
- 195°F Max. Temperature
- 250V, 15.0A
- 9.2 oz Weight

Product No.	Description
PSW	3/8" BSP-M Connect (Brass)
PSW1	1/4" BSP-M Connect (Brass)
PSW1SS	1/4" BSP-M Connect (Stainless Steel)
29004824P	Repair Kit
12500100P	Switch

Speedmatic



- 3000 psi Max. Pressure
- 725 psi Switching Pressure
- 3/8" BSP-M Connection
- 0" to 1.18" (30 mm) Stroke
- 39.37" Cable Length
- Automatic RPM regulator for gas engines

Product No.	Description
SPEEDMATIC	RPM Regulator

Float Tank Design Recommendations

