



Foaming Brush Swivels



- For low pressure operation
- All Brass Construction
- Self-locking hose barb

Product No.	Connection Type
SW7010	3/8" M x 3/8" - 2 Barbs
SW7016	1/2" M x 1/2" - 2 Barbs

90° Boom Swivels



- 3000 psi Rated Pressure
- 7.0 gpm Max. Flow
- 300°F Max. Temperature
- 360° Swivel Action
- Viton O-rings

Product No.	Connection Type
SW7030	3/8" Brass
SW7035	3/8" Stainless Steel
RKSW	Repair Kit (SW7035)
SW7030K	Repair Kit (SW7030)

High Pressure Swivels



- 3000 psi Rated Pressure
- 200°F Max. Temperature
- Brass Construction
- Stainless Steel Insert

Product No.	Connection Type
SW7080	3/8" MPT x 3/8" FPT
SW7480	1/4" MPT x 1/4" FPT
RKSW	Repair Kit (SW7080)
SW7480K	Repair Kit (SW7480)

90° Hose Reel Swivels



- 3000 psi Max. Pressure
- 10.0 gpm Max. Flow
- 300°F Max. Temperature
- Brass Construction
- Viton O-rings

Product No.	Connection Type
SW7475	1/2" FPT x 1/2" FPT
SW7475K	Repair Kit

Light Duty Swivels



- 3650 psi Rated Pressure
- 195°F Max. Temperature
- Brass

Product No.	Connection Type
26100010P	3/8" NPT-M x 3/8" NPT-F

90° High Pressure Swivels



- 3650 psi Rated Pressure
- 10.5 gpm Max. Flow
- 195°F Max. Temperature
- Stainless Steel

Product No.	Connection Type
SW9014	1/4" BSP-M x 1/4" BSP-F
SW9038	3/8" BSP-M x 3/8" BSP-F
26130524P	Repair Kit

High Pressure Swivels



- 5000 psi Rated Pressure
- 200°F Max. Temperature
- Stainless Steel Construction
- Stainless Steel Insert

Product No.	Connection Type
SW7044	3/8" MPT x 3/8" FPT
SW7470	1/4" MPT x 1/4" FPT
RKSW	Repair Kit (SW7044)
SW7480K	Repair Kit (SW7470)

High Pressure Swivels



- 5100 psi Rated Pressure
- 10.5 gpm Max. Flow
- 320°F Max. Temperature
- Stainless Steel

Product No.	Connection Type
SW3500	3/8" MPT x 3/8" FPT
SW5114	1/4" MPT x 1/4" FPT
SW3500BR	3/8" MPT x 3/8" FPT Brass 3650 psi
26106250P	1/4" MPT x 3/8" FPT
26105324P	Repair Kit

NEW!

High Pressure Swivels



- 8700 psi Rated Pressure
- 15.8 gpm Max. Flow
- 210°F Max. Temperature
- Stainless Steel


Product No.	Connection Type
SW600	3/8" BSP-F x 3/8" BSP-F

90° High Pressure Swivels



- 5100 psi Rated Pressure
- 21.0 gpm Max. Flow
- 195°F Max. Temperature
- Stainless Steel

Product No.	Connection Type
SW9012	1/2" BSP-M x 1/2" BSP-F
26132524P	Repair Kit



swivels components

Mosmatic WDB/WDC Swivel



- 4000 psi Max. Pressure
- 250°F Max. Temperature
- Maximum 30 RPM
- 90° Swivel Action
- Stainless Steel

Typical Applications:

- Automatic carwash systems, hose reels, ceiling booms

Product No.	Connection Type
MM43252	3/8" NPT-F x 3/8" NPT-M
MM43353	1/2" NPT-F x 1/2" NPT-M
MM43354	1/2" NPT-F x 1/2" NPT-F

Mosmatic WDR/WDRL Swivel



- 3000 psi Max. Pressure
- 180°F Max. Temperature
- Stainless Steel
- Dual bearing system

Typical Applications:

- Automatic carwash systems, hose reels, ceiling booms

Product No.	Connection	Fits Gun Type
MM41920	1/2" NPT-F x 1/2" NPT-M	Hydro Spray, Cobra/Mark VII, Aqua Jet (old)
MM41462	1" NPT-F x 1" NPT-F (110 RPM)	Fits PDQ, Laserwash
MM43904	WD/WC - Repair kit	

Mosmatic DGV Gun Swivel



- 4000 psi Max. Pressure
- 250°F Max. Temperature
- Maximum 30 RPM
- Stainless Steel

Typical Applications:

- High pressure gun, lance or hip line.

Product No.	Connection Type
MM32552	1/4" NPT-M x 1/4" NPT-F
MM32564	3/8" NPT-M x 3/8" NPT-F

Mosmatic DGS Gun Swivel



- 4000 psi Max. Pressure
- 250°F Max. Temperature
- Maximum 30 RPM
- Stainless Steel

Typical Applications:

- Ceiling booms, hose connections, high pressure cleaners

Product No.	Connection Type
MM30153	3/8" NPT-M x 3/8" NPT-F
MM30154	3/8" NPT-F x 3/8" NPT-F

Mosmatic DYT Swivel



- 5000 psi Max. Pressure
- 50°F Max. Temperature
- Maximum 2000 RPM
- Stainless Steel

Typical Applications:

- Surface Cleaners

Product No.	Connection Type
MM59153	3/8" NPT-F x 3/8" NPT-M

Mosmatic DYG Swivels



- 4000 psi Max. Pressure
- 250°F Max. Temperature
- Maximum 2000 RPM
- Stainless Steel

Typical Application:

- Ceiling booms, hose connections, high pressure cleaners, floor cleaners

Product No.	Connection Type
MM57051	1/4" NPT-F x 1/4" NPT-M
MM57153	3/8" NPT-F x 3/8" NPT-M

Mosmatic DGK Gun Swivels w/Hose Barb



- 4000 psi Max. Pressure
- 250°F Max. Temperature
- Maximum 30 RPM
- Stainless Steel

Typical Applications:

- Hose connections, guns (inlet), any application requiring an easy turning connection.

Product No.	Connection Type
MM32181	3/8" NPT-M x 1/4" hose barb
MM32182	3/8" NPT-M x 5/16" hose barb
MM32189	3/8" NPT-M x 3/8" hose barb