

pumps

equipment

Professional Water Transfer Pumps



- Powered by Honda engines for extra reliability
- Protective metal roll-cage on 2", 3" & 4" pumps give added strength for everyday jobsite use
- Cast-aluminium pump housing offers protection & portability
- Extra-strength carbonceramic mechanical seals for heavy-duty jobsite use
- Handles solids up to 1/4" (7mm) in diameter
- Made In Japan



1" PWP Water Transfer Pump.



2" - 4" PWP Water Transfer Pumps

Product No.	Engine	Port Size	Max.Capacity	Suction Lift	Max.Head	Net Weight
PWP1H	1.0 hp Honda 4-stroke GX25 OHC	1" x 1" (11 T.P.I)	33 USG/min (125 L/min)	26.2' ft (8 m)	114' ft (35 m)	10 lbs
PWP2HX	4.0 hp Honda GX120 OHV	2" x 2"	158 USG/min (600 L/min)	28' ft (8.5 m)	113' ft (34 m)	52 lbs
PWP3HX	5.5 hp Honda GX160 OHV	3" x 3"	290 USG/min (1100 L/min)	28' ft (8.5 m)	105' ft (32 m)	60 lbs
PWP4HX	8.0 hp Honda GX240 OHV	4" x 4"	476 USG/min (1800 L/min)	26.2' ft (8 m)	105' ft (32 m))	103 lbs


Professional Semi Trash Pumps



- Powered by Honda GX-series engines for reliability
- Super-tough design handles slurry & solids up to 3/4" in diameter
- Heavy-duty silicon carbide mechanical seal for longlasting performance
- Cast-iron volute and impeller for heavy-duty performance
- Made In Japan

Product No.	Engine	Port Size	Max.Capacity	Suction Lift	Max.Head	Net Weight
PWP2SST	4.0 hp Honda GX120 OHV	2" x 2"	185 USG/min (700 L/min)	28' ft (8.5 m)	76 ft (23 m)	46 lbs
PWP3SST	5.5 hp Honda GX160 OHV	3" x 3"	264 USG/min (1000 L/min)	28' ft (8.5 m)	76' ft (23 m)	59 lbs

Professional Trash Pumps



- Powered by Honda GX-series engines for reliability
- Cast-iron impeller and volute delivers strength and performance
- Clears solids up to 1" in diameter
- Heavy-duty silicon carbide mechanical seal for longlasting performance
- Removable front-cover for easy cleaning and on-site maintenance
- Made In Japan

Product No.	Engine	Port Size	Max.Capacity	Suction Lift	Max.Head	Net Weight
PWP2SWT	5.5 hp Honda GX160 OHV	2" x 2"	158 USG/min (600 L/min)	26' ft (8 m)	80 ft (24 m)	74 lbs
PWP3SWT	8.0 hp Honda GX240 OHV	4" x 4"	343 USG/min (1300 L/min)	26' ft (8 m)	93' ft (28 m)	132 lbs
PWP4SWT	11.0 hp Honda GX340 OHV	3" x 3"	530 USG/min (2000 L/min)	26' ft (8 m)	93' ft (28 m)	147 lbs

Maritimes/Quebec/Ontario


Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

C10

www.pressurewashcomponents.ca

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592
Fax TOLL FREE: 1.800.661.3719



PWP2MBI5.5 Economical Water Pump



- 5.5hp Briggs & Stratton Engine
- Port Size: 2" x 2"
- Max.Capacity: 140 gpm
- Suction Lift: 26 ft (8 m.)
- Max. Head: 90'
- Weight: 74 lbs
- Heavy duty, cast aluminum pump
- Cast Iron Impeller
- Pump bolted to frame for extra durability
- Full frame with top protective bar
- Mechanical seal with ceramic face
- Strainer, hose clamps & rubber seals included

Product No.	Description
PWP2MBI5.5	2" Economical Water Pump

PWP2SCH5050 High Head Pump



- 5.5 hp Honda GX160 OHV
- Port Size: 2" x 2"
- Max.Capacity: 106 gpm
- Suction Lift: 26 ft (8 m)
- Max. Head: 165 ft (50 m)
- Weight: 59 lbs
- Ideal for irrigation, firefighting, or any applications where higher discharge heights are necessary.
- Fire Kit available separately
- Made in Japan

Product No.	Description
PWP2SCH5050	2" High Head.Pump

PWP2P5GC Poly Pump



- 5.0 hp Honda GC160 OHV
- Port Size: 2" x 2"
- Max.Capacity: 158 gpm
- Suction Lift: 20 ft (6 m)
- Max. Head: 125' (38 m)
- Weight: 46 lbs
- EPDM seals and stainless steel hardware for extra resistance to corrosive chemicals
- Perfect for liquid fertilizing and other chemical spraying applications
- Assembled in Canada

Product No.	Description
PWP2P5GC	2" Chemical Resistant Poly Pump

PWP3SMD Diaphragm Sludge Pump



- 5.5 hp Honda GX160 OHV
- Port Size: 2" x 2"
- Max. Capacity: 65 gpm
- Max Head: 50ft. (16 m)
- Suction Lift: 26 ft (8 m)
- Weight: 99 lbs
- Treats solids up to 1.2" (31mm) diameter
- Positive displace design makes priming quick & easy
- Ideal solution for use with slow seepage situations and sludge or water with high solid content
- Heavy duty cast aluminium pump body with tubular steel full protective cage for use on tough jobsites
- 4 anti-vibration rubber feet underneath base to protect pump assembly
- Rubber diaphragm and check valve are easy to replace for reduced down time and maintenance
- Made in Japan

Product No.	Description
PWP3SMD	3" Diaphragm Sludge Pump



equipment

pump accessories & submersible pumps

Portable Water Pumps - Accessories



Aluminum Pump Kit w/Frame

Poly Pump Kit

Product No.	Description
-------------	-------------

Pump Kits

PWP2LE	2" Aluminum Pump Kit with Frame
PWP3LE	3" Aluminum Pump Kit with Frame
PWP34300637	Poly Pump Kit with Stainless Steel Hardware (less engine)



2" Long Thin Strainer

2" Polyethylene Strainer

2" Round Hole Strainer

Strainers

PWP-LS200	2" Long Thin Strainer
PWP-PS200	2" Polyethylene Strainer
PWP-RS200	2" Round Hole Strainer



PWP1MFKIT Fire Hose Kit

2" High Head Hose Kit

2" Discharge Hose w/Poly C & E Couplers



PVC Discharge Hose

2" EPDM Suction Hose

Suction Hose

Hoses

PWP1MFKIT	Fire Hose Kit for 1" Water Pump
PWP2SCH5050-HK	Hose Kit for 2" High Head Pump
DH2POLY	2" x 50 ft Discharge Hose w/Poly C & E Couplers
DH2PVC	2" x 50 ft Discharge Hose
DH3PVC	3" x 50 ft Discharge Hose
SH2POLY	2" x 50 ft Suction Hose EPDM w/Poly C & E Couplers
SH2PVC	2" x 20 ft Suction Hose
SH3PVC	3" x 20 ft Suction Hose



1.5" NSPM Polycarbonate Fog Nozzle

Nozzles

FNWP	1.5" NSPM Polycarbonate Fog Nozzle
------	------------------------------------

PSP200SSD Submersible Dewatering Pump



- 0.5 hp, 115V, 6A induction electric motor
- Port Size: 2" NPT
- Max.Capacity: 67 gpm
- Max. Head: 37'
- Weight: 33 lbs
- Unique design with double silicon carbide mechanical-seals offers added protection for extended life
- Cast-iron volute and impeller combine to add weight and-performance to submersible design
- Specially-treated components extend rust protection for longer working times and low-maintenance needs
- CSA-certified for guaranteed safe performance under tough conditions

Product No.	Description
PSP200SSD	2" Submersible Dewatering Pump

PSP125SSU Submersible Utility Pump



- 1/3 hp, 115V, 3A induction electric motor
- Discharge Size: 1-1/4"
- Max.Capacity: 2160 gph
- Max. Head: 27'
- Weight: 9 lbs
- Motor with thermal overload protection
- Built-in thermal overload reset
- Top discharge with garden hose connection
- Bottom suction down to 1/8"
- Use your standard garden hose as a discharge hose. Just connect and go!
- Ideal for watering your garden, back-up basement flooding, emptying pool covers or hot tubs
- CSA-certified for guaranteed safe performance under tough conditions

Product No.	Description
PSP125SSU	1" Submersible Utility Pump