



Car Wash Series 76 Triplex Plunger Pump



Forged brass manifold with lifetime warranty. Oversized connecting rods for maximum life. Solid ceramic plungers with continuously lubricated packings.

- Max. Inlet Pressure:** 125 psi
- Max. Fluid Temperature:** 165° F
- Inlet Port Thread:** 1.0" - 11 BSP-F
- Discharge Port Thread:** 3/4" - 14 BSP-F
- Shaft Diameter:** 1.378 in./35.0 mm
- Pump Dimensions:** 15.6" x 14.0" x 9.5"
- Max. Inlet Vacuum:** 9 ft. Water (7.9 in Hg)
- Crankcase Oil Capacity:** 91.0 oz.

Product No.	GPM	PSI	RPM	Bore	Stroke	HP	Weight
CW81	21	1200	1000	1.417 in./36mm	1.102 in./28 mm	16.5 EBHP	92.0 lbs
CW61	17	1200	1000	1.417 in./36mm	0.945 in./24 mm	13.2 EBHP	92.0 lbs

Car Wash Series 77 Sixplex Plunger Pump



Forged brass manifold with lifetime warranty. Most widely used pump frame in the touchless car wash industry. Dual manifolds utilizing a common crankcase for efficient performance.

- Max. Inlet Pressure:** 125 psi
- Max. Fluid Temperature:** 165° F
- Inlet Port Thread:** 1.0" - 11 BSP-F
- Discharge Port Thread:** 3/4" - 14 BSP-F
- Shaft Diameter:** 1.378 in./35.0 mm
- Pump Dimensions:** 22.1" x 14.0" x 9.7"
- Max. Inlet Vacuum:** 9 ft. Water (7.9 in Hg)
- Crankcase Oil Capacity:** 64.0 oz.

Product No.	GPM	PSI	RPM	Bore	Stroke	HP	Weight
CW1541	41	1200	1000	1.417 in./36mm	1.102 in./28mm	33.8 EBHP	156.0 lbs